

DISTRIBUTION ACCESSORIES



HYDRAULIC FLASH ARRESTORS

CONCOA Hydraulic Flash Arrestors are designed to provide flashback control in fuel gas piping systems. Equipped with floor stands and flashback fluid, the equipment protects against common accidents such as reverse flow, flashback, and hose burn. Multiple line size and flow rate options combined with robust materials of construction provide the reliability and safety required in industrial fuel gas systems.



836 0037 Shown



836 0038 Shown

DISTRIBUTION SYSTEMS

Features	Materials of Construction	Specifications
1" or 1-1/2" Connections Excellent flow capacity 300 or 1000 SCFH max flow rate Application flexibility 20 PSIG Relief Pressure Safe and reliable control	Tank Carbon Steel Inlet/Outlet Connections Carbon Steel	Maximum Flow at 15 PSIG 300 SCFH (141.6 LPM) 1000 SCFH (471.9 LPM) Inlet/Outlet Connections 1" MNPT (300 SCFH version) 1-1/2" MNPT (1000 SCFH version) Relief Pressure 20 PSIG Weight 55 lbs (300 SCFH version) 123 lbs (1000 SCFH version)

Ordering Information			
Part Number	Gas Service	Inlet/Outlet	Relief Pressure
836 0037	Acetylene	1" MNPT	20 PSIG
836 0038	Acetylene	1-1/2" MNPT	20 PSIG