

# ALARMS

## ADVANTIUM 1&2 PLUS REMOTE ALARMS



5750013-01-000 shown

5750023-01-000 shown

The new Advantium Series offers superior integration, protection, and convenience by allowing end-users to monitor normally open or closed contact devices with a single flip of a switch.

Features	Materials	Specifications
<p><b>Two Input Channels (Advantium 2 PLUS)</b> Monitors both primary and reserve banks</p> <p><b>One Input Channel (Advantium 1 PLUS)</b> Monitors one source</p> <p><b>Dry Contact Relay Outputs</b> Connect to building or auxiliary systems</p> <p><b>NO or NC Switch Compatibility</b> Customize system signals</p> <p><b>Auto-reset on Cylinder Replenishment</b> No button to push</p> <p><b>Ability to “Daisy Chain” Multiple Alarms</b> Notify multiple users of alarm</p> <p><b>Switch Selectable 40-Minute Alarm Delay</b> Allow for transient events</p> <p><b>CE Marked</b> Conforms to EU directives</p>	<p><b>Enclosure</b> Polycarbonate injection molding Flame retardant UV stabilized with mold release RoHS compliant</p>	<p><b>Audio</b> 93db audible alarm</p> <p><b>Power Input</b> 90~264 VAC, 47-63 Hz (US, UK European, Australian, and Chinese adapters included)</p> <p><b>Outputs</b> 2 channels (Advantium 2 PLUS) 1 channel (Advantium 1 PLUS) Dry contacts Normally open/normally closed (selectable) Contact rating .5A 24V</p> <p><b>Inputs</b> 2 channels Accepts normally open/normally closed contact closure (selectable) Resettable fuse protection</p> <p><b>Dimensions</b> 4.75 x 7.5”x 2.625” (120.65mm x 190.5mm x 66.675mm)</p>

## Ordering Information

Part Number	Description
5750023-01-000	Advantium 2 PLUS remote alarm (universal input)
5750013-01-000	Advantium 1 PLUS remote alarm (universal input)
5295316-XX	Input Cable Assembly available in 3', 10', 25', 50' and 100' lengths. "XX" in order number denotes length.
5295329-XX	Interconnect Cable Assembly available in 3', 10', 25', 50' and 100' lengths. "XX" in order number denotes length.
5295312	Intrinsic safety Barriers for 515, 526 and 527 Series switchover systems and 529 protocol alarm station
5295296	Intrinsic safety Barriers for 522, 523, 537 Series switchover systems
5295319-XX	Cables for intrinsic safety Barriers (two required)